

PP & PE for Caps & Closures



Braskem 

Our purpose is to improve people's lives by creating sustainable solutions through chemicals and plastics.

In line with the **UN 2030 sustainable development goals**, Braskem took on long-term goals with people and the planet in 2020. Working in three priority and four complementary dimensions, we are looking to achieve these goals through innovation.



Eliminating plastic waste



Mitigating Climate Change



Social Responsibility & Human Rights

An **ecosystem** developed to represent Braskem's **products, technologies** and **initiatives** that **help drive the circular economy**.



All our polypropylene grades are available with **ISCC+ certification**, using the **mass balance method with bio, circular or bio-circular feedstocks***, ensuring sustainability and traceability across the supply chain.

Caps & Closures

Braskem's **PP and PE resins are designed for** high-performance caps and closures across **beverage, food, personal care, and household applications**. Developed to meet key functional requirements such as dimensional stability, hinge durability, and organoleptic performance, our materials offer efficient solutions for injection and compression molding—**enabling lighter, more convenient packaging**. Braskem's comprehensive portfolio helps customers develop innovative, cost-effective closures with reliable processing and consistent quality, **creating value throughout the entire supply chain**.



Food Packaging Applications




Carbonated Soft Drinks

Braskem's resins for CSD caps are formulated to withstand **high internal pressure** and **ensure secure sealing, supporting both injection and compression molding** to enable design flexibility and processing efficiency.



Mineral Water

To meet strict organoleptic standards, Braskem offers **high-purity resins with low migration potential**, developed using advanced technology to **prevent taste, odor, or color changes** - earning trust from the most demanding mineral water brands.



Beverages

Braskem provides versatile resin solutions for a wide range of beverage applications, from **dairy and juices to hot-filled teas and energy drinks**. Our materials support high processing **efficiency** and **design adaptability**, helping customers meet performance, safety, and shelf-life requirements.



Food

Braskem's polyethylene and polypropylene resins offer **excellent safety, compatibility**, and performance for food applications, including **complex closures like large flat-area** and bicomponent caps, supporting regulatory compliance and consumer confidence.

Non-Food Packaging Applications



Personal Care

Braskem delivers polypropylene resins with **excellent surface finish, transparency, and gloss**, ideal for visually appealing personal care caps such as **flip-tops and disk-tops**. Our materials ensure design flexibility, aesthetic quality, and reliable molding performance.



Home Care

Braskem's polyethylene and polypropylene resins offer **high chemical resistance, dimensional stability, and processing efficiency for home care closures like flip-top, push-pull, and threaded caps** - supporting **durable, user-friendly packaging** across diverse formulations and shelf lives.



Industrial Use

For demanding industrial applications, Braskem's resins provide **mechanical strength, chemical resistance, and tight sealing performance** to meet rigorous safety standards. Our low-density polyethylene solutions enable the flexibility needed for retractable and specialty closures.

► Caps & Closures - PP

	Typical Properties	Melt Flow Index (230°C / 2,16 Kg)	Flexural Modulus	Tensile Strength at Yield	Notched Charpy Impact Resistance @23°C	Notched Charpy Impact Resistance @-20°C	Haze *	Additives **
	Method	ISO 1133	ISO 178	ISO 527-1	ISO179	ISO 179	ASTM D1003	-
	Units	g/10 min	MPa	MPa	kJ/m ²	kJ/m ²	%	-
Homo	FT120WV	12	1850	38	-	-	-	N, AS
	Flip-top caps, excellent dimensional properties							
	HSP250NA	25	1650	36	3	-	-	N, AS
	Caps for general use							
	H7058-25R	25	1400	33	3	-	-	CR
	Caps for general use, narrow MWD							
Random	DH789.01	50	1700	37	2,5	-	-	N, AS
	Thin wall caps, fast cycle							
	H734-52RNA2	52	1800	37	2,5	-	-	N, AS, CR
	Thin wall caps, fast cycle, narrow MWD							
	RSP100NA	10	1200	28	6	-	8	N, AS
	High transparency injection molded caps, flip-top							
RSP230NA	23	1200	29	5	-	8	N, AS	
High transparency injection molded caps, flip-top								
Inspire® 364	42	1050	27	5,5	-	8	N, AS	
High transparency and thin wall injection molded caps								
Inspire® 382	70	1050	27	5	-	10	N, AS	
High transparency and thin wall injection molded caps								
RSP100NAR	100	1050	27	4,5	-	9	N, AS, CR	
High transparency and thin wall injection molded caps								
ICP	EP445L	6	1600	30	7,2	3,3	-	N, AS, S, CR
	Caps for carbonated soft drinks, water, juices							
	C706-21NAHP	21	1500	27	8	4,5	-	N, AS
	Injection molded caps for general use, with thin wall, fast cycle and excellent stiffness							
	C7082-30NA	30	1400	25	8,5	4	-	N, AS
	Injection molded caps for general use, with thin wall and fast cycle							
	C705-44NAHP	44	1500	28	7	4	-	N, AS
	Injection molded caps for general use, with thin wall and fast cycle							
CD700NAQ	70	1200	24,5	8	3,5	-	N, AS, CR	
	Injection molded caps for general use, with thin wall and fast cycle, large flat area thin wall , excellent dimensional stability , narrow MWD							
CG700NA	70	1350	23,5	6	3,5	-	N, AS	
	Injection molded caps for general use, with thin wall and fast cycle, large flat area thin wall , excellent dimensional stability							
C7069-100NA	100	1500	28	4	2,5	-	N, AS	
Injection molded caps for general use, with thin wall and fast cycle, large flat area thin wall , excellent dimensional stability								

*Injection molded specimen according to ISO 294. **Additives: N = Nucleated/Clarified, AS = Antistatic, CR = Controlled Rheology; S = Slip Agent

► Caps & Closures - PE*

	Typical Properties	Melt Flow Index (230°C / 2,16 Kg)	Density	Additives**
	Method	ASTM D1238	ASTM D792 / D1505	-
	Units	g/10 min	g/cm ³	-
HDPE	HD6401H	0,8	0,955	S
		Carbonated soft drinks		
	Bio-based SGE7252NS	2	0,952	-
		Beverage bottle caps		
	HC7260	7,2	0,959	-
		Still water, edible oil		
	Bio-based SHC7260	7,2	0,959	-
		Still water, edible oil		
	HDI2061	20	0,955	-
		Large flat caps, spouts		
HA7260	20	0,955	-	
	Large flat caps, spouts			
Bio-based SHA7260	20	0,955	-	
	Large flat caps, spouts			
LDPE	BC818	8.3	0,918	-
		General use, bung		
	Bio-based SBC818	8.3	0,918	-
		General use, bung		
	LDI2020	20	0,920	-
		General use, bung		
Bio-based SPB208	22	0,923	-	
	Large flat caps, snap lids			
Bio-based SPB608	30	0,915	-	
	Large flat caps, snap lids			
LLDPE	IF33	48	0,931	-
		Edible oil, home and personal care, bungs		

*All PE grades are subject to availability. **Additives: S = Slip Agent

Braskem

Global Presence

With a **global, human-oriented vision of the future**, Braskem strives every day to improve people's lives by creating sustainable solutions in chemistry and plastics. Braskem is the largest producer of thermoplastic resins in the Americas and a **global leader in the production of biopolymers on an industrial scale**.

Our products are exported to some **70 countries** and we count on 40 Industrial units, located in Brazil, the United States, Germany and Mexico (in partnership with Mexican company Idesa). For more information, visit www.braskem.com.



Clients in
more than
70
countries

More than
8.500
team
members

6th
largest producer in PE,
PP and PVC

#1 producer PE, PP and PVC
in the Americas

#1 PP producer in North America

#1 PE, PP and PVC producer
in Latin America

40
industrial units:


29 plants


4 plants


5 plants


2 plants

- Braskem does not make and expressly disclaims any warranties, including warranties of merchantability or suitability for a particular purpose, regardless of whether oral or written, expressly or implied, or allegedly arising from any use of any trade or from any course of dealing in connection with the use of the information contained herein or the product itself. The data provided in this document is limited to the extent of Braskem's knowledge and/or supplier's information provided to Braskem on this date.
- This Product should not be used in medical or pharmaceutical applications classified as (i) Class IV under applicable Brazilian law or (ii) Class III under applicable EU law or (iii) highest level risk under applicable United States law (i.e., those applications presenting maximum risk to health and safety of patient, operator, consumer or third parties).
- It is the Purchaser's responsibility to verify the suitability of Braskem's Product for the intended use, to obtain the necessary competent government approvals and to ensure compliance with any applicable legal and regulatory requirements. Moreover, Purchaser acknowledges and accepts the responsibility to determine and perform all necessary tests on its finished products to ensure that all conditions, specifications, legal and regulatory requirements are met and that its finished products manufactured with this Product are suitable for the application intended, including, but not limited to, medical, pharmaceutical, food packaging, food contact, as applicable.
- For the purposes of this document, Braskem shall be understood as Braskem S.A and its subsidiaries, including Braskem Netherlands B.V., Braskem Europe GmbH and Braskem America Inc., and the Braskem legal entity(ies) which is/are the seller of Product, unless otherwise expressly specified.

Webpage:

braskem.com

